


PRODUCT SPECIFICATION

R6P-PVC



Dimensions



Super Heavy Duty Battery

Specifications

Chemical System: Zinc-Manganese Dioxide (Zinc Chloride Electrolyte)

IEC Name: R6P
ANSI/NEDA: 15D(AA)
Camelion Model: R6P
Average Weight: 14g

Dimension(ΦxH) 14.0±0.5 x 50.0±0.5mmm 0.56 ±0.02 x 1.97 ±0.02 inch

Terminals: Flat
Nominal Voltage: 1.5Volts
Capacity: 960mAh

(Rated at 25mA to 0.8V)

Operating Temperature: -18℃-55℃
Storage Temperature: 15℃-25℃
Relative Humidity: 60±15%
Jacket: PVC

Usage Guide



Flashlight



Clock



Radio

Cautions

Storage

Store the battery in a cool, dry and well-ventilated area.

Handling

- 1) Never charge the battery. Do not heat or disposed in fire or water. Do not modify or disassemble the battery. Do not short-circuit positive (+) and negative (-) terminals. Keep away from metal or other conductive materials.
- 2) Keep away from infants. If infant happens to swallow the battery, consult a doctor immediately.
- 3) When the battery is stored or disposed, isolate positive (+) and negative (-) terminals of the battery to avoid those terminals touch each other.
- 4) In case the battery electrolyte happen to come into mouth,gargle well enough and consult a doctor immediately.

Notice:

Environmental elements comply with 2006/66/EC requirements. This information is subject to change without prior notice and for reference only. It should not be used as a basis for a product guarantee or warranty. For additional information, please consult your nearest Camelion Sales Office or Distributor or visit our website at: www.camelionbattery.com.





R6P-PVC


Super Heavy Duty Battery


ANSI/IEC Standard Testing


Typical characteristics 21 ℃














Notice: